


**ULTRA
ITALIA**
LUXURY WOOD FINISH


JUBILANT
AGRI & CONSUMER PRODUCTS



PU Clear | PU White | PU Colour | Water Based PU 1K | Water Based Natural Finishes 2K
Parquet | Acrylic | Polyester | Special Effects | Epoxy | Rubbing Compound | Wood Filler

PU CLEAR

LUXURY WOOD FINISH



Ultra Italia PU is universal wood coating made in Italy by Verinlegno and imported by Jubilant Agri and Consumer Products. Italian wood finishes are best in class finishes delivering exquisite craftsmanship and sheer elegance.

Ultra Italia Clear PU is available in 4 variants of gloss level which are HIGH GLOSS, SEMI GLOSS, MATT G30 & CLASSIC G10. All top coats have a common under coat Ultra Italia Clear Sealer.





FEATURES



Quick
Drying



Hardness



Clarity of
Image



Protection

APPLICATION PROCESS

PRE PAINTING STEPS: Sand the wooden surface along the grains using sand paper 180, and then 320 or 400. Wipe surface to clean off loose dust particles.

Product Application	Mixing Ratio of Base+ Hardener (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step-1 UI PU Clear Sealer 1 st Coat	2:1	UI Matt & Sealer Thinner	25 - 35%	Spray	4-6 Hours
Sand the surface with sand paper 240 or 320 and wipe clean					
Step-2 UI PU Clear Sealer 2 nd Coat	2:1	UI Matt & Sealer Thinner	25 - 35%	Spray	4-6 Hours
Sand the surface with sand paper 240 or 320 and wipe clean, apply 3 rd coat if required before top coat application					
Step-3 UI PU Clear Top Coat 1 st Coat	Gloss 1:1	UI PU Thinner for Gloss	25 - 35%	Spray	4-6 Hours
	Semi Gloss 2:1	UI Matt & Sealer Thinner			
	Matt 2:1				
	Classic G10 2:1				
Sand the surface with sand paper 400 or 600 and wipe clean					
Step-4 UI PU Clear Top Coat 2 nd Coat	Gloss 1:1	UI PU Thinner for Gloss	25 - 35%	Spray	4-6 Hours
	Semi Gloss 2:1	UI Matt & Sealer Thinner			
	Matt 2:1				
	Classic G10 2:1				

PU WHITE

LUXURY WOOD FINISH



Ultra Italia PU is universal wood coating made in Italy by Verinlegno and imported by Jubilant Agri and Consumer Products. Italian wood finishes are best in class finishes delivering exquisite craftsmanship and sheer elegance.

Ultra Italia White PU is available in 2 variants which are HIGH GLOSS, MATT G30. All top coats have a common under coat Ultra Italia White Sealer.





FEATURES



Quick
Drying



Hardness



Non Yellow
Coating



Protection

APPLICATION PROCESS

Product Application	Mixing Ratio of Base+ Hardener (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step-1 UI PU White Sealer 1 st Coat	2:1	UI PU Thinner for Matt & Sealer	25 - 35%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step-2 UI PU White Sealer 2 nd Coat	2:1	UI PU Thinner for Matt & Sealer	25 - 35%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean, apply 3 rd coat if required before top coat application					
Step-4 UI PU Pigmented Gloss / Matt 1 st Coat	Gloss 1:1 / Matt 2:1	UI PU Thinner for Gloss / Matt	25 - 35%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step-5 UI PU Pigmented Gloss / Matt 2 nd Coat	Gloss 1:1 / Matt 2:1	UI PU Thinner for Gloss / Matt	25 - 35%	Spray	4 Hours

PU COLOUR COATINGS



Ultra Italia PU Colour Coatings are known for its durability and resistance to wear and tear. These coatings are commonly used in industrial and commercial settings for their protective properties, as they provide a tough layer of protection against scratches, abrasion, and chemicals.

One of the key benefits of Ultra Italia PU colour coatings is their versatility. They come in a wide range of colours and finishes, from glossy to matte, and can be applied to create a smooth, uniform appearance. Additionally, they can be formulated to meet specific performance requirements, such as resistance to UV light, heat, and moisture.

Overall, Ultra Italia PU Colour Coatings are a reliable and long-lasting option for protecting surfaces and providing a high-quality finish.





FEATURES



More than 4200+
everlasting shades.



High in
Durability



Resists Cracking
Even on Curved
Surfaces



Superior
Scratch & Stain
Resistance



Superior
Heat
Resistance

APPLICATION PROCESS

Product Application	Mixing Ratio Base + Hardener (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step 1 UI PU White Sealer 1 st Coat	2:1	UI Thinner for Matt & Sealer	25 - 35%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step 2 UI PU White Sealer 2 nd Coat	2:1	UI Thinner for Matt & Sealer	25 - 35%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean, apply 3 rd coat if required before top coat application, sand with sand paper 320 or 400 and wipe clean					
Step 3 UI PU Pigmented Gloss / Matt 1 st Coat	Gloss 1:1 / Matt 2:1	UI Thinner for Gloss / Matt	25 - 35%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step 4 UI PU Pigmented Gloss / Matt 2 nd Coat	Gloss 1:1 / Matt 2:1	UI Thinner for Gloss / Matt	25 - 35%	Spray	4 Hours

WATER BASED PU 1K

LUXURY WATER BASED WOOD FINISH



Ultra Italia PU Interior Matt is a popular option because it protects your furniture from nature's elements and has low VOC and odour.

Protecting your furniture from the exterior weather conditions Ultra Italia Water based PU Exterior is a highly flexible, UV-resistant coating that keeps wood safe from the sun, water, and yellowing.

With this incredibly durable product for your exteriors, you may finish painting your furniture twice as quickly.

FEATURES



Low VOC
Odour



Premium
Aesthetics



Quick
Drying



Easy
Application





APPLICATION PROCESS

WATER BASED 1K INTERIOR

Product Application	Mixing Ratio Base + Hardener (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step 1 UI WB SS INT G10 / G30 1 st Coat	NA	Water	0 - 10%	Spray/ Brush	6-8 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step 2 UI WB SS INT G10 / G30 2 nd Coat	NA	Water	0 - 0%	Spray/ Brush	6-8 Hours
Sand the surface with sand paper 320 or 400 and wipe clean, apply 3 rd coat if required					

WATER BASED 1K EXTERIOR

Product Application	Mixing Ratio Base + Hardener (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step 1 UI WB impregnator	NA	Water	NA	Spray/ Brush	2-4 Hours
Step 2 UI WB EXT SLR 1 st coat	NA	Water	0 - 10%	Spray/ Brush	4-8 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step 3 UI WB EXT SLR 2 nd coat	NA	Water	0 - 10%	Spray/ Brush	4-8 Hours
Sand the surface with sand paper 320 or 400 and wipe clean, apply 3 rd coat if required					
Step 4 UI WB EXT G30 1 st coat	NA	Water	0 - 10%	Spray/ Brush	Over Night
Step 5 UI WB EXT G30 2 nd coat	NA	Water	0 - 10%	Spray/ Brush	Over Night

WATER BASED PU 2K

LUXURY WATER BASED WOOD FINISH



Ultra Italia Water-Based 2K PU is a self-sealing top coat that comes in a variety of matt levels G0, G03 to G30.

Ultra Italia Water Based 2K PU for interiors is a completely green product-it is practically odourless and exceeds European criteria for low volatile organic compounds.





FEATURES



Low VOC
Odour



Premium
Aesthetics



Hardness



Quick
Drying



Easy
Application

APPLICATION PROCESS

WATER BASED 2K PU

PRE PAINTING STEPS: Sand the wooden surface along the grains using sand paper 180, and then 320 or 400. Wipe surface to clean off loose dust particles.

Product Application	Mixing Ratio Base + Hardener (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step 1 UI WB WB 2K G0 / G03 /G30 1 st Coat	G0 - 85:15 G03 - 90:10 G30 - 95:05	Water	5 - 20%	Spray / Paint Roller	3-4 Hours
Sand the surface with sand paper 240 or 400 and wipe clean					
Step 2 UI WB WB 2K G0 / G03 /G30 2 nd Coat	G0 - 85:15 G03 - 90:10 G30 - 95:05	Water	5 - 20%	Spray / Paint Roller	3-4 Hours
Sand the surface with sand paper 240 or 400 and wipe clean					
Step 3 UI WB WB 2K G0 / G03 /G30 3 rd Coat	G0 - 85:15 G03 - 90:10 G30 - 95:05	Water	5 -20%	Spray / Paint Roller	3-4 Hours
Apply fourth coat if required, sand with sand paper 240 or 400 and wipe clean					

PARQUET

LUXURY WATER BASED WOOD FINISH



Parquet Floor Coat features a special abrasion resistant and tough surface. The product renders a Rich Natural Matt finish to the wooden floor. It has high distinctiveness of image, leading to an accentuated grain pattern and offers best in class durability.

The product is a water-based 2 component transparent self-sealer with excellent elasticity, hardness and resistance to abrasion. The addition of the hardener up to 5% improves its chemical resistance to staining. It is suitable on all kinds of wood.





FEATURES



Low VOC
Odour



Anti
Skid



Hardness



Quick
Drying



Easy
Application

APPLICATION PROCESS

PRE PAINTING STEPS: Sand the wooden surface along the grains using sand paper 180, and then 320 or 400. Wipe surface to clean off loose dust particles.

Product Application	Mixing Ratio of Base (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Parquet First Coat	95:05	Water	0 - 25%	Use spray gun or paint roller	Overnight
Sand the surface with sand paper 240 or 400 and wipe clean					
Parquet Second Coat	95:05	Water	0 - 25%	Use spray gun or paint roller	8 Hours
Sand the surface with sand paper 240 or 400 and wipe clean					
Parquet Third Coat	95:05	Water	0 - 25%	Use spray gun or paint roller	8 Hours
Apply fourth coat if required, sand with sand paper 240 or 400 and wipe clean.					

ACRYLIC

LUXURY WOOD FINISH



Ultra Italia Acrylic Polyurethane (PU) coatings are widely used in the wood industry to provide durable and attractive finishes for furniture, cabinetry, and flooring. Known for their quick drying time and excellent protective qualities, Acrylic PU coatings resist scratches, stains, and moisture, making them ideal for high-traffic areas. Their UV resistance ensures long-lasting colour retention, suitable for both interior and exterior applications. The versatility of Acrylic PU allows for various finishes, contributing to aesthetic flexibility. Overall, Acrylic PU coatings enhance the durability and appearance of wood products, making them a popular choice in the wood industry.

Ultra Italia Acrylic Clear is available in 4 top coat variant of gloss which are **High Gloss, G30, G10 & G5 (dead matt)**





FEATURES



Best suitable for light coloured woods



It provides a rich natural look



Maximum level of transparent coating



Excellent Aesthetic Quality

APPLICATION PROCESS

PRE PAINTING STEPS: Sand the wooden surface along the grains using sandpaper 180, and then 320 or 400. Wipe surface to clean off loose dust particles.

Product Application	Mixing Ratio of Base (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Acrylic Sealer 1 st Coat	80:20	UI Matt & Sealer Thinner	25 - 35%	Spray	Overnight
Sand the surface with sandpaper 240 or 320 and wipe clean					
Acrylic Sealer 2 nd Coat	80:20	UI Matt & Sealer Thinner	25 - 35%	Spray	Overnight
Sand the surface with sandpaper 240 or 320 & wipe clean, apply 3 rd coat if required before top coat application					
Acrylic Top Coat 1 st Coat	Glossy 50:50	NA	0	Spray	Overnight
	G30 80:20	UI Matt & Sealer Thinner	25 - 35%		
	G10 80:20				
	G5 85:15				
Sand the surface with sandpaper 400 or 600 and wipe clean					
Acrylic Top Coat 2 nd Coat	Glossy 50:50	NA	0	Spray	Overnight
	G30 80:20	UI Matt & Sealer Thinner	25 - 35%		
	G10 80:20				
	G5 85:15				

Ultra Italia Acrylic Clear is available in 4 top coat variant of gloss which are High Gloss, G30, G10 & G5 (Dead Matt). For the all four top coat we can use UI Acrylic Clear Sealer as undercoat .

POLYESTER

LUXURY WOOD FINISH



Ultra Italia Polyester Coating, for high-gloss reflective surfaces that have along-lasting gloss. Get a radiant mirror-like finish with great depth and high reflection. Polyester coatings react with the accelerator and catalyst, generating a high resistant film that bestows the surface with a superior hardness.

Mainly suitable for closed-pore top coats, this coating makes it possible to attain a coating film with excellent chemical/physical resistance, that is easy to sand and is subject to restricted shrinkage over time.





FEATURES



Excellent mirror
like shine



Fast-drying



High solid
content



High chemical/
physical resistance



Easy to sand
and buff

APPLICATION PROCESS

Product Application	Mixing Ratio of Base (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step 1 UI Epoxy Clear Combo	1:1	NA	NA	Spray	1-2 Hrs
If required, light sanding can be done with sand paper 320 or 400 and wipe clean					
Step 2 UI Polyester (Polyester 100: Hardener 02: Accelerator 01)	100:2:1	NA	NA	Spray	10 Mins*
Wet on wet					
Step 3 UI Polyester (Polyester 100: Hardener 02: Accelerator 01)	100:2:1	NA	NA	Spray	10 MINS*

Apply 6-8 coats of UI Polyester as per the above steps buffing is necessary to get the required gloss. Buffing should be carried out after 48 hours of application of last coat.

BUFFING

1. Sand the surface with sand paper 220 to remove the waxy layer from coating and to get smooth surface.
2. Further sand with sand paper 440 followed by 600.
3. Carry out wet sanding with sand paper 600 followed by sand paper 800 and 1000 and 1200 and 1500 and 2000.
4. Carry out buffing using buffing compounds and buffing machine to get the required gloss.

METAL EFFECT

SOPHISTICATION AND ELEGANCE IN
INTERIORS WITH METAL FINISHES



Metal has the merit to give that touch of luxury, originality and brightness to any place. The metallized effect allows to reproduce, as accurately as possible, the shade of different metals.

Gold and Silver for a refined and timeless choice, Bronze for a vintage effect and Aluminium with an elegant and almost retro charm.





Silver



Gold



Aluminium



Bronze

The effect can be coated with Acrylic Topcoat to get Matt and Gloss finish

FEATURES



Best in class
strength &
durability



Fine
finish



Metallic
shades

APPLICATION PROCESS

Product Application	Mixing Ratio of Base (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
Step 1 UI PU White Sealer 1 st Coat	2:1	UI PU Thinner for Matt & Sealer	40 - 50%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step 2 UI PU White Sealer 2 nd Coat	2:1	UI PU Thinner for Matt & Sealer	40 - 50%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean, apply 3 rd coat if required before top coat application, sand with sand paper 320 or 400 and wipe clean					
Step 3 UI Metal Effect 1 st Coat (Gold/Silver/Bronze/Aluminium)	83:17	UI PU Thinner for Gloss	40 - 50%	Spray	after 1 Hour within 2 Hour
Do not sand the metallic coat					
Step 4 UI PU Clear Gloss/Matt 1 st Coat	Gloss 1:1 / Matt 2:1	UI PU Thinner for Gloss / Matt	40 - 50%	Spray	4 Hours
Sand the surface with sand paper 320 or 400 and wipe clean					
Step 5 UI PU Clear Gloss/Matt 2 nd Coat	Gloss 1:1 / Matt 2:1	UI PU Thinner for Gloss / Matt	40 - 50%	Spray	4 Hours

SPECIAL EFFECTS

LUXURY BESPOKE FINISHES



Unleash the Power of Ultra Italia Special Effects on Wood! From radiant shimmer to otherworldly glow, explore a range of transformative finishes that push the boundaries of creativity. We provide a wide range of special effects which are Chrome, Ceramic, Marble, Cloudy Pearl, Mother of Pearl & Filament Effect, and other four Metal Effects -Silver, Gold, Aluminium, Bronze effects. Let your woodwork radiate with uniqueness and awe-inspiring beauty!

Ultra Italia Special Effects:

CHROME
CERAMIC
MARBLE
CLOUDY PEARL
MOTHER OF PEARL
FILAMENT



CHROME



MATERIAL, ESSENTIAL AND VERSATILE

Shiny, bright, apparently perfect: for a "pure" surface, with no defects. With a great aesthetical impact.

CERAMIC



MINIMALIST URBAN TASTE

This Ceramic Effect creates immediately an urban style, but, at the same time, a warm and welcoming atmosphere.


MARBLE



AN EVERLASTING STYLE, AN EVERLASTING BEAUTY

Sophisticated natural marbles revive, creating a timeless language, which matches with contemporary design with a unique elegance and harmony.

CLOUDY PEARL



THE LIGHTNESS OF CLOUDS

This utilizes chromatic interplay to produce gentle variations of lighter colours against darker backgrounds, interact with light and yielding distinctive visual effects.


MOTHER OF PEARL



THE INEVITABLE CLASSIC

The MOP gives to the surfaces the precious aspect typical of mother-of-pearl through reflexes which convey a feeling of precious modernity.

FILAMENT



REFINED DESIGN

Glowing, seductive, harmonious: the distinguishing and timeless elegance of briar wood. A unique and unmistakable style.

PREMIUM WOOD STAINS

16 EXQUISITE SHADES



Ultra Italia premium wood stains with 16 shades are transformative coatings that infuse wooden surfaces with an array of hues, from warm oak tones to deep ebony shades. They seep into the wood's fibers, emphasizing its natural patterns while shielding it from environmental factors.





NATURAL



FRESH TEAK



INDIAN WALNUT



AMERICAN WALNUT



BLACK



WENGÉ



DARK INDIAN OAK



YELLOW OAK



RED BROWN



ROSE WOOD



FRESH GREEN



ORANGE



LIGHT GOLDEN OAK



ANTIQUÉ PINE



**DARK RED
MAHOGANY**



**DARK BROWN
MAHOGANY**

RUBBING COMPOUND

SINGLE STEP RUBBING AND
BUFFING COMPOUND



Ultra Italia single-step rubbing and buffing compound designed for the furniture industry simplifies the polishing process. Specially designed for removal of 1500 & 2000 grit sanding scratches in wood coatings. Efficiently removing scratches and enhancing the finish in one application. Crafted with abrasives and polishing agents, it streamlines both production and restoration, providing a convenient solution for achieving a smooth and glossy appearance with minimal effort and time. This specialized compound is a user-friendly and effective tool for enhancing the aesthetic appeal of wooden furniture surfaces.

FEATURES



Removes scratch
marks



Easy to spread




Machine use &
hand use



Excellent
gloss

APPLICATION PROCESS



STEP-1

Wet sand the cured
coated surface with
sand paper grit 1500/
2000.



STEP-2

Wet sand the cured
coated surface with
sand paper grit 1500/
2000.



STEP-3

Wet sand the cured
coated surface with
sand paper grit 1500/
2000.



STEP-4

Wet sand the cured
coated surface with
sand paper grit 1500/
2000.

WOOD FILLER

LUXURY WOOD FILLER



Ultra Italia Wood Filler is a single-component, water-based, zero-smell dent filler and grain filler designed for various wood and wood-type substrates. This innovative wood filler offers a convenient and odour-free solution for repairing dents and filling grain in wood surfaces. With its water-based formulation, it provides easy application and cleanup, making it user-friendly.

Available in three shades - teak, walnut, and white - Ultra Italia Wood Filler offers versatility to complement different wood finishes seamlessly. Whether you're working on furniture, cabinetry, or other wooden surfaces, this filler provides an effective means of achieving a smooth and flawless appearance. Its one-component nature simplifies the application process, allowing for efficient and hassle-free repairs.

FEATURES



Excellent
adhesion



Ideal for small
repair



Fitting nail
holes



Mixable with
colour powder

APPLICATION PROCESS


Application tool - Putty Spatula

Thinning* - Ready to use. (if required should be done with water)



STEP-1 Surface Preparation

The surface must be clean, free from all loose materials, dust, dirt, oil and any other contaminants.



STEP-2 Application

Apply UI wood filler on the clean surface for small repairs, minor surface defects and filling nail holes.



STEP-3 Remove excesses filler

Allow the UI Wood Filler to dry for about 1-2 hrs and. Sand the surface with sand paper 180-320.

EPOXY

LUXURY WOOD FINISH



UI EPOXY IS A 2 component product used for treatment of wood and its derivatives before Wood Coating application begins.

FEATURES



Protection from
moisture of wood



Prevents Oil leaching
from wood



Prevents peeling off
coatings

APPLICATION PROCESS

Product Application	Mixing Ratio Base + Hardener (By Vol.)	Thinner	Thinner Dilution % (By Vol)	Application Method	Recoating Period (Hrs.)
UI Epoxy Clear Combo	1:1	NA	NA	Spray/ Ragging	1-2 Hrs

COLOUR TINTING SYSTEM


A₂-100% Automatic Dispenser



➡ 100% Recirculation

1 100% Recirculation

Zero nozzle dryness/blockage;
purge-free;
maintenance-free;
colorant saving;
stable accuracy.



2 Calibration-free Piston Pump



3 Piston Rod Detection

Warning when the piston is not pushed down.



<p>↓</p> <p>P1 Piston Pump Sequential Dispensing</p>		<p>■ Flow Rate 600ml/min</p> <p>■ Efficiency 200ml/min</p>
<p>■ Minimum Shot 1/384Y(0.077ml)</p>		<p>■ Pump Capacity 60ml</p> <p>■ Stirring Speed 20rpm</p>
<p>■ Canister Size 1.8L / 2.3L POM 2.3L / 3.8L Stainless Steel (Optional)</p> <p>■ NO. of Canisters Up to 16</p>		
<p>■ Max Can Size (D X H) 320X600mm</p> <p>■ Machine Dimension (W X D X H) 707X848X1300mm</p>		
<p>■ Net Weight 130kg</p> <p>■ Gross Weight 155kg</p>		<p>■ Power ≤ 100W</p> <p>■ Power Supply 220V/110V 50Hz/60Hz</p>

SHADE CARD



RAL K7



The RAL CLASSIC K7 colour collection has been essential for the precise communication of colours in the paints, chemicals and automotive industry for over 80 years.

- Fan deck size 5.0 x 15.0 cm compact and perfect size for matching.
- Colour illustration 2.0 x 5.0 cm for each of the 216 shades.
- Five colors on each page of the RAL shade card to view the color contrast effectively.
- This in a Gloss Color format shade card.

RAL D2



The RAL D2 fan deck shows all 1,825 colours of the RAL DESIGN system on 9 colours per page. The finding of colour shades is facilitated due to the arrangement of colours by the criteria hue (H), lightness (L) and chroma (C). The foundation of the RAL DESIGN system is the the CIELAB colour space, which is internationally used since 1976.

NCS



NCS-1950 Color sample collection of 1,950 color references

- Arranged in 5 sets: greyscale, yellow (G80Y-Y70R), red (Y80R-R70B), blue (R80B-B70G) and green (B80G-G70Y)
- Stiff binder
- 216 pages, 10 colors per page
- Languages: English



POLYURETHANE PU FINISH

Known for its aesthetic appeal and inspiring elegance, it is available in both matt and gloss finish in clears, whites and 4200+ shades using tinting machine. It has best in class scratch, heat, stain and chemical resistance.

ACRYLIC FINISH

This finish provides best in class transparency, elasticity and resistance to yellowing. Available in matt and gloss finish and are suitable for both interior and exterior surfaces.

POLYESTER FINISH

It offers a mirror like gloss finish. It is particularly suitable for application where high film thickness is required. The finish is rebuffable for restoring the gloss after a few years.

WATER BASE FINISH

Specially formulated to provide reduced emissions and most suited for renovation projects and exterior applications due to their higher durability. It has higher coverage and shorter application time. Overall the finish is both user and environment friendly.

SPECIAL EFFECT FINISH

We provide to our customers a wide range of special effects which are Chrome, Ceramic, Marble, Cloudy Pearl, Mother of Pearl & Filament Effect, and other four Metal Effects -Silver, Gold, Aluminium, Bronze effects.



Jubilant Agri and Consumer Products Limited

Plot No. 142, Chimes, 3rd Floor, Sector 44,
Gurugram, Haryana - 122003 India.
Tel: +91-120-6290100 Website: www.ultraitalia.com

Scan to visit
Ultra Italia



Whatsapp

